

Water to Water Source Heat Pumps—3 to 35 Tons

- Heating only, cooling only or heating and cooling models
- High efficiency and quiet operation
- R-22 or non-CFC, R-407C refrigerant
- Large panels for accessibility to compressor and controls sections
- Flexible configurations with top or side piping (120–420)
- Flexible configurations with front or side control box (120–420)
- Status lights—compressor 1, compressor 2, fault (120–420)
- Domestic hot water coil (036–072)

For more detail, refer to Catalog 1111. For the most current information, refer to www.mcquay.com.

Model GRW—extended range heating and cooling models

Model GHW—extended range heating only models

Model GCW—extended range cooling only models



Capacity and Physical Data

Model sizes	Btuh nominal cooling	Cabinet dimensions, inches			Water connections	
		Width	Depth	Height	Load/source	Domestic hot water
036	36,000	28 1/8	28 1/8	19	3/4" FPT	1/2" FPT
048	48,000	28 1/8	28 1/8	21	1" FPT	1/2" FPT
060	60,000	28 1/8	28 1/8	21	1" FPT	1/2" FPT
072	72,000	35 1/8	28 1/8	21	1" FPT	1/2" FPT
120	120,000	34	42	41	1 1/2	N/A
150	150,000	34	42	41	1 1/2	N/A
180	180,000	34	42	41	2	N/A
240	240,000	34	50	63 1/8	2	N/A
300	300,000	34	50	63 1/8	2	N/A
360	360,000	34	50	63 1/8	2	N/A
420	420,000	34	50	63 1/8	2	N/A